



Silverwood 1950



Mocha 2011 with Cream 0032 5mm Feature Strip



Truffle **2010** 457mm x 457mm



Mocha **2011** 457mm x 457mm



Taupe **2012** 457mm x 457mm



Latte **2013** 457mm x 457mm



Ivory **2014** 457mm x 457mm



Riverstone **2015** 457mm x 457mm



Ivory **2014** with Cream **0032** 5mm Feature strip



Riverstone **2015** with Cream **0032** 5mm Feature strip

### Feature Strips

Applying a 5mm feature strip between the tiles in either a complementary or a contrast colour can create a classic yet stylish look

Cream 0032



Gold 0026



Silver 0025



Mid Grey 5752



Copper 0033



Terracotta 0034



Brown 0031



Black 0028



expona supertile







supertile

The subtle shades of Ivory and Mocha create a bright and inviting atmosphere







Truffle **2010** with Black **0028** 5mm Feature Strip







Blond Limed Oak **1912**

203mm x 1219mm



Coromandel **1960**

184mm x 1219mm



Honey Limed Oak **1964**

203mm x 1219mm



Jarrah **1959**

184mm x 1219mm



Brown Limed Oak **1913**

203mm x 1219mm



Antique **1955**

152mm x 1219mm



Honey Oak **1914**

184mm x 1219mm



Light Pine **1963**

152mm x 1219mm



Oak **1958**

184mm x 1219mm



Rimu **1928**

184mm x 1219mm



Red Oak **1948**

203mm x 1219mm



Victorian Ash **1961**

184mm x 1219mm



Silverwood **1950**

203mm x 1219mm



Ghost Gum **1953**

203mm x 1219mm

**exponA** superplan**K**





Brown Limed Oak **1913**



Blond Limed Oak **1912**



superplank

The limed effect in Brown, Blond and Honey shades tone down or bring out the contrasts giving the area an interesting appeal



superplank

Silverwood and Ghost Gum offer a contemporary look to complement a range of décors



Silverwood **1950**









Antique **1955**



Coramandel **1960**





superplank

The grain of Oak, Red Oak and Honey Oak provides a classic and timeless impression







Oak **1958**



Honey Oak **1914**



Rimu **1928**



Victorian Ash **1961**



superplank

The patterns and textures of Rimu, Light Pine and Victorian Ash add character and charm to a room



# CUSTOMER

# GUARANTEE

All products purchased from the range are guaranteed for a full 15 years against normal wear and tear in a residential environment and 10 years in a commercial environment provided they have been fitted correctly and maintained in accordance with the manufacturer's instructions.\*

In order to make a claim, customers must apply in writing indicating where their flooring was purchased and provide satisfactory proof of purchase.

This guarantee only applies in the event of the visible wearing out of the decorative pattern on the surface within the 15 year Residential or 10 year Commercial guarantee period from the time of purchase, provided the flooring has been subject to normal usage in the recommended environment.

It does not cover general misuse, and we suggest that adequate UV protection be taken against products being installed in direct sunlight as fading may occur. It is the manufacturer's recommendation that felt or teflon pads are used for protection under chairs and other furniture which will help to prevent scratching and marring of your floor's finish.

When moving any heavy objects please place a plywood panel over your vinyl floor.

In the event of the manufacturers of Expona Superplank or Supertile accepting that a claim is valid under this guarantee, they will either repair the flooring or supply replacement flooring free of charge. In the unlikely event of the flooring no longer being in stock, then flooring of equivalent quality will be provided.

**\*These guarantees are provided by the manufacturer and are in addition to other rights and remedies of the consumer under a law in relation to the goods. Our goods come with guarantees that cannot be excluded under the Australian Consumer Law. You are entitled to a replacement or refund for a major failure and compensation for any other reasonably foreseeable loss or damage. You are also entitled to have the goods repaired or replaced if goods fail to be of acceptable quality and the failure does not amount to a major failure.**



**PHTHALATE  
FREE**

## Green Tag <sup>Cert</sup>™ Certified Flooring

Polyflor's Expona Superplank & Supertile has achieved a GreenTag <sup>Cert</sup>™ SILVER Plus Rating, meaning it has a Very Good status as a sustainable product that is healthy for use in any home or commercial project. Global GreenTag <sup>Cert</sup>™ is the only ACCC (Australian Competition and Consumer Commission) approved National Certification Mark in the green building materials sector. Meaning you can be sure that you are purchasing a product that is independently certified as environmentally preferred.

Green Tag <sup>Cert</sup>™ is an independent third party, green product rating and certification ecolable, underpinned by rigorous scientific and Life Cycle Assessment (LCA) processes. In short, Green Tag <sup>Cert</sup>™ helps the consumer identify products that are environmentally preferred, for use in their home via an independently audited and industry recognised whole of life cycle certification system. Ecospecifier's Green Tag <sup>Cert</sup>™ is recognised by the Green Building Council of Australia (GBCA) and the New Zealand Green Building Council (NZGBC).

[gbca.org.au](http://gbca.org.au)  
[nzgbc.org.nz](http://nzgbc.org.nz)



Scan this QR code for further information about GreenTag <sup>Cert</sup>™















All Expona LVT (Luxury Vinyl Tile & Plank) products, including Superplank & Supertile, are 100% recyclable and are recycled in Australia and New Zealand through the Recofloor - Vinyl Take Back Scheme.

The Recofloor scheme reduces the amount of vinyl flooring going to local landfill. Through the localised scheme, flooring off-cuts from the installation process are recycled back into new flooring. Uplifted or end of life material is downcycled into traffic calming products such as traffic cone and road barrier bases.

Tile & Plank patterns may contain variations in markings and shading as part of their design. By following a policy of continuous development, we reserve the right to add or delete patterns and improve technical specifications without prior notice. Reproductions in printing and photography are for guidance only, they give a general indication of colour and are not necessarily representative of the overall effect or design. For colour selection an original sample is recommended.



TECHNICAL DATA	Characteristics	Standards	Unit	EXPONA SUPERTILE	
 <p>Heterogeneous vinyl floorcovering available as tiles based on a phototechnical reproduction with a transparent wear layer and a factory applied polyurethane surface treatment for contract application.</p>     <p>EN 649</p>	<b>Type of floorcovering</b>	EN 649		heterogeneous, PVC	
	<b>Surface treatment</b>				
	<b>Description</b>				tile with bevelled edges
	<b>Colours</b>				6
	<b>Performance classification</b>	EN 685			23, 33, 42
	<b>Gauge</b>	EN 428	mm		2,5
	<b>Wear layer thickness</b>	EN 429	mm		0,55
	<b>Tile size</b>	EN 427	mm		16 @ 457mm x 457mm = 3.34m <sup>2</sup>
	<b>Residual indentation</b>	EN 433	mm		≤0,1
	<b>Colour fastness to artificial light</b>	ISO 105-BO2 method 3	level		≥6
	<b>Behaviour to fire</b>	EN 13501-1			B <sub>FL</sub> - S1
	<b>Slip resistance</b>	DIN 51130 EN 13893			R10 DS
	<b>Impact sound reduction</b>	EN 140-8	dB		ca. 4
	<b>Resistance to thermal conductivity</b>	DIN 52612	m <sup>2</sup> k/w		0,02
	<b>Assessment of static electrical propensity</b>	EN 1815	kV		<2
	<b>Electrical resistance to earth</b>	EN 1081	Ohm		ca. 10 <sup>11</sup>
	<b>Leakage to earth</b>	VDE 0100 §24	Ohm		> 5 x 10 <sup>4</sup>
<b>Chemical resistance</b>	EN 423			*	
<b>Abrasion group</b>	EN 649			T	
<b>Castor chair suitability</b>	EN 425			yes, type W, EN 12 529	
<b>Underfloor heating suitability</b>				suitable max. 27° C	

TECHNICAL DATA	Characteristics	Standards	Unit	EXPONA SUPERPLANK	
 <p>Heterogeneous vinyl floorcovering available as planks based on a phototechnical reproduction with a transparent wear layer and a factory applied polyurethane surface treatment for contract application.</p>     <p>EN 649</p>	<b>Type of floorcovering</b>	EN 649		heterogeneous, PVC	
	<b>Surface treatment</b>				
	<b>Description</b>				plank
	<b>Colours</b>				14
	<b>Performance classification</b>	EN 685			23, 33, 42
	<b>Gauge</b>	EN 428	mm		2,5
	<b>Wear layer thickness</b>	EN 429	mm		0,55
	<b>Plank sizes</b>	EN 427	mm		18 @ 152mm x 1219mm = 3.34m <sup>2</sup> 15 @ 184mm x 1219mm = 3.37m <sup>2</sup> 14 @ 203mm x 1219mm = 3.46m <sup>2</sup>
	<b>Residual indentation</b>	EN 433	mm		≤0,1
	<b>Colour fastness to artificial light</b>	ISO 105-BO2 method 3	level		≥6
	<b>Behaviour to fire</b>	EN 13501-1			B <sub>FL</sub> - S1
	<b>Slip resistance</b>	DIN 51130 EN 13893			R10 DS
	<b>Impact sound reduction</b>	EN 140-8	dB		ca. 4
	<b>Resistance to thermal conductivity</b>	DIN 52612	m <sup>2</sup> k/w		0,02
	<b>Assessment of static electrical propensity</b>	EN 1815	kV		<2
	<b>Electrical resistance to earth</b>	EN 1081	Ohm		ca. 10 <sup>11</sup>
	<b>Leakage to earth</b>	VDE 0100 §24	Ohm		> 5 x 10 <sup>4</sup>
<b>Chemical resistance</b>	EN 423			*	
<b>Abrasion group</b>	EN 649			T	
<b>Castor chair suitability</b>	EN 425			yes, type W, EN 12 529	
<b>Underfloor heating suitability</b>				suitable max. 27° C	

\* Resistance depending on concentration and time of exposure, in case of increased impact of oils, grease, acids, alkalis and other aggressive chemicals - please contact Polyflor.



Honey Limed Oak 1964




Riverstone 2015 with Black 0028 5mm Feature Strip



**Polyflor Australia Pty Ltd**  
 ABN 68 007 134 518

59-65 Wedgewood Road,  
 Hallam VIC 3803  
 Australia  
 P: 1800 777 425  
 F: 03 9215 4444  
 E: sales@polyflor.com.au

[www.polyflor.com.au](http://www.polyflor.com.au)



10/13