

4












Dark toned oaks create the feeling of depth and warmth

















Patterned effects add character and interest to a room

FLOORING COLLECTION

PRODUCT RANGE

	14 - C.	10-50		1		P. The second
Nordic White Oak 3007	184mm x 1219mm	Elm 3023	152m	ım x 914mm	Washed Oak 3022	152mm x 914r
and the second	<i>t</i> : .		Į T			
Blond Oak 3032	152mm x 914mm	Radiata Pine	2202 102m	nm x 914mm	Baltic Pine 2208	102mm x 914
			-			
Vintage Timber 3046	152mm x 914mm	Grey Driftwoo	od 3009 152m	nm x 914mm	Rustic Oak 3008	184mm x 1219
		1. an 11				
Wild Chestnut 3012	152mm x 914mm	Burnt Rustic V	Vood 3014 152m	nm x 914mm	Dark Classic Oak 3036	184mm x 1219
			in the		Feature Strips Applying a 5mm feature str in either a complementary	
Brown Limed Oak 3005	184mm x 1219mm	Kings Oak 30	006 184mr	m x 1219mm	can create a classic yet sty Cream 0032	
					Gold 0026	
	1. 1.		and the second	1.	Silver 0025	
	1.53	- Maria	S. Property	m2	Mid Grey 5752	
			All Provent		Copper 0033	
	1000	a long		1	Terracotta 0034	
		P. Sterlin	91.335	14 - 3 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1	Brown 0031	
White Sandstone 23	28 Natural Limes 457mm x 457m		Grey Limestone 457mm x 457mm	2327	Black 0028	
the second se						

CUSTOMER GUARANTEE

Camaro Flooring Collection luxury vinyl tiles & planks have been developed to meet the highest technical specifications

certification ecolabel, underpinned by rigorous scientific and Life Cycle Assessment (LCA) processes. In short, Green TagTM helps the consumer Ideal for all areas of the home, the collection ensures high performance and optimum style. In addition, Camaro Flooring Collection is suitable for identify products that are environmentally preferred, for use in their home moderate commercial applications such as light traffic areas within hotels, conference rooms and small offices. Compared with many natural flooring via an independently audited and industry recognised whole of life cycle options, Camaro Flooring Collection will, under normal conditions resist certification system. Ecospecifier's Green Tag™ is recognised by the Green household stains, will not crack, chip or splinter. By following our simple Building Council of Australia (GBCA) and the New Zealand Green Building maintenance instructions, your floor will look great for years to come. Council (NZGBC). To learn more visit www.ecospecifier.com.au, www.gbca. org.au or www.nzgbc.org.nz

From a collection of 20 colour and style options as well as the additional accessories, we are confident you will own a floor design to be proud of. The manufacturers of the Camaro Flooring Collection are confident that Recofloor-Vinyl Take Back Scheme Camaro LVT (Luxury Vinyl Tile) products are 100% recyclable and are their high quality products will provide many years of valuable service. All recycled in Australia and New Zealand through the Recofloor – Vinyl Take products purchased from the range are guaranteed for 15 years against normal wear and tear in the recommended environment, provided that Back Scheme they have been fitted correctly and maintained in accordance with the manufacturer's instructions. In order to make a claim, customers must The Recofloor scheme reduces the amount of vinyl flooring going to apply in writing, indicating where their flooring was purchased and provide local landfill. Through the localised scheme, flooring off-cuts from the installation process are recycled back into new flooring. Uplifted or end of satisfactory proof of purchase. life material is down cycled into traffic calming products such as traffic cone This guarantee only applies in the event of visible wearing out of the and road barrier bases.

decorative pattern on the surface within 15 years of purchase, providing the flooring has been subject to normal usage in the recommended environment.

It does not cover general misuse and we suggest that adequate UV protection be taken against products being installed in direct sunlight as fading may occur. It is the manufacturer's recommendation that felt or teflon pads are used for protection under chairs and other furniture which will help to prevent scratching and marring of your floor's finish.

When moving any heavy objects please place a plywood panel over your vinyl floor.

In the event of the manufacturers of Camaro Flooring Collection accepting The tiles are installed as per AS/NZ1884 to a suitable surface using the that a claim is valid under this guarantee, they will either repair the flooring environmentally friendly Kiesel brand 'Star100' adhesive'. or supply replacement flooring free of charge.

It is important to remember to 'condition' the tiles in the room where they In the unlikely event of the flooring no longer being in stock, then flooring are to be laid for 24 hours at a temperature between 18-24 degrees C, of equivalent quality will be provided. both prior to installation and after installation.

Recommended Use Areas

Residential - only suitable for use in interior of the home. Camaro Flooring Keeping your Camaro Flooring Collection tiles and planks clean and attractive is a simple task with PUR Surface Protection. Sweeping or Collection should not be used in constantly wet areas. vacuuming regularly removes dust and dirt from the floor. Simply wash with **Environmentally Certified Flooring** your normal mopping system and a neutral detergent cleaner. A polish is The Camaro product has achieved Ecospecifier's world leading 'Green not required and could in fact make the floor slippery. Remember, regular and light cleaning is the best way to keep your Camaro Flooring Collection Tag ${}^{\mbox{\scriptsize TM}\prime}$ certification. Meaning you can be sure that you are purchasing a looking perfect.

product that is independently certified as environmentally preferred. Green Tag™ is an independent third party, green product rating and

TECHNICAL DATA	Characteristics	Standards	CAMARO	
CAMARO	Type of floorcovering	EN 649	heterogeneous, PVC	
	Surface treatment		PUR	
	Gauge	EN 428	2.0mm	
Endergoalter	Wear layer thickness	EN 429	0.3mm	
	Packaging plank size	EN 427	36 @ 102 x 914mm = 3.34m ² 24 @ 152 x 914mm = 3.34m ² 15 @ 184 x 1219mm = 3.37m ²	
	Packaging tile size	EN 427	16 @ 457 x 457mm = 3.34m ² 18 @ 304 x 609mm = 3.34m ²	
Recofloor"	Colour fastness to artificial light	EN ISO 105-B02	level > 6 method A	
	Behavior to fire	EN 13501-1	B _{fl} - s1	
(15)	Slip resistance	DIN 51130 EN 13893	R10 DS	
	Castor chair suitability	EN 425	yes	
	Underfloor heating suitability	EN 1264-2	suitable max. 27º C	

Reproductions in printing and photography are for guidance only. For colour selection, an original sample is recommended.

Installation and Maintenance

Full instructions for both installation and maintenance are detailed on the leaflet that is contained in every box of Camaro Flooring Collection. If you require a copy of this leaflet or further guidance, please contact: Polyflor Australia on 1800 777 425 or Polyflor New Zealand on 0800 765 935

Installation

Installation of Camaro Flooring Collection is relatively straightforward and should be carried out by a suitably qualified floor layer.

Maintenance







Polyflor Australia Pty Ltd ABN 68 007 134 518

59-65 Wedgewood Road Hallam VIC 3803 Australia P: 1800 777 425 F: 03 9215 4444 E: sales@polyflor.com.au

www.polyflor.com.au



100 Plunket Avenue

Manukau Auckland 2104 New Zealand P: 0800 765 935 F: 0800 846 737 E: sales@polyflor.co.nz

www.polyflor.co.nz

