

CARPET TILE SPECIFICATION	NEWLINE - PANTHER	NEWLINE	AVENUE	GRID & MATRIX
TILE SIZE	500mm x 500mm	500mm x 500mm	500mm x 500mm	500mm x 500mm
CARPET STYLE TYPE	Textured loop	Textured loop	Textured loop	Level loop
FIBRE TYPE	100% Nylon BCF SDN	100% Nylon BCF	100% Nylon BCF SDN	100% Nylon BCF
GAUGE	1 / 12	1 / 12	1 / 12	1 / 10
PILE WEIGHT GRMS / MT2 +/-5%	600G / M2 (21 ounces)	650G / M2 (23 ounces)	500G / M2 (18 ounces)	480G / M2 (17 ounces)
PILE HEIGHT HIGH PILE MM +/-5%	4.5MM	4.5MM	4.0MM	3.2MM
PILE HEIGHT LOW PILE MM +/-5%	3.0MM	3.0MM	2.0MM	-
STICTHES PER 10CM +/-5%	42	37	42	55
TOTAL THICKNESS OF TILE MM +/-5%	6.5MM	6.5MM	6.0MM	5.8MM
BACKING TYPE	PVC WITH FIBRE GLASS	PVC WITH FIBRE GLASS	BITUMEN	PVC WITH FIBRE GLASS
GLUE DOWN (Kiesel Okatmos star 150)	YES	YES	YES	YES
SQUARE MTS PER CARTON	5 SQUARE MTS	5 SQUARE MTS	5 SQUARE MTS	6 SQUARE MTS
PACKING NO TILES IN CARTON	20 PCS	20 PCS	20 PCS	24 PCS
CROCKING AND COLOUR FASTNESS	Passed QB/T2755-2005	Passed QB/T2755-2005	Passed QB/T2755-2005	Passed QB/T2755-2005
DIMENSIONAL STABILITY	Passed QB/T2755-2005	Passed QB/T2755-2005	Passed QB/T2755-2005	Passed QB/T2755-2005
FLAMMABILITY	Passed ISO 9239-1	Passed ISO 9239-1	Passed ISO 9239-1	Passed ISO 9239-1
ANTI STATIC TREATED	YES	YES	YES	YES
ANTI SOIL TREATED	YES	YES	YES	YES