INITIAL CONSTRUCTION CLEAN

- Sweep, mop sweep or dry vacuum the floor to remove dust, grit and debris.
- Apply a solution of alkaline cleanser, diluted to the manufacturer's
 instructions, to the floor and leave for sufficient time to react with the
 soiling. Using a 165 rpm rotary machine fitted with a rotary scrubbing
 brush or, if necessary, a scrubbing pad, machine scrub the floor and then
 pick up the slurry with a wet vacuum. Rinse the floor thoroughly with
 clean, warm water, pick up with a wet vacuum and leave to dry thoroughly.
- Note 1: For small areas, where there is no suitable scrubbing machine available, a deck scrubber should be used in conjunction with a wet vacuum or mop and bucket system.
- Note 2: For very heavy soiling, dilution rates above the manufacturer's minimum recommendations may be necessary.
- Note 3: For Polysafe Hydro and Hydro Evolve, the scrubbing pad should be replaced with a rotary scrubbing brush or a cylindrical type scrubbing machine.



ROUTINE MAINTENANCE

 The frequency of each of the operations is dependent upon the type and intensity of traffic.

STANDARD SURFACE FINISH

- Sweep, mop sweep or dry vacuum the floor to remove dust and loose dirt.
- Spot mop regularly. Stubborn black marks can be removed by using the centre disc of a scrubbing pad and a small amount of undiluted alkaline cleanser. Place the disc under the sole of a shoe and rub - this gives greater pressure. Rinse the area well with clean warm water and leave to dry.
- Apply a solution of neutral or alkaline cleanser, diluted to the
 manufacturer's instructions, to the floor and leave for sufficient time
 to react with the soiling. Using a 165 rpm rotary machine fitted with a
 rotary scrubbing brush or, if necessary, a scrubbing pad, machine scrub
 the floor and then pick up the slurry with a wet vacuum. Rinse
 thoroughly with clean, warm water, pick up with a wet vacuum and leave
 to dry thoroughly.

POLYSAFE HYDRO AND HYDRO EVOLVE

- Sweep, mop sweep or dry vacuum the floor to remove dust and loose dirt.
- Spot scrub regularly with a deck scrubber.
- Apply a solution of neutral or alkaline cleanser, diluted to the
 manufacturer's instructions, to the floor and leave for sufficient time
 to react with the soiling. Using a 165 rpm rotary machine fitted with a
 bristle brush, cylindrical machine or deck scrubber, scrub the floor and
 then pick up the slurry with a wet vacuum. Rinse thoroughly with clean,
 warm water, pick up with a wet vacuum and leave to dry thoroughly.



APPLICATION OF A FLOOR DRESSING

 A floor dressing or maintainer containing polish should not be applied to the Polysafe ranges, as this may impair the slip resistance but, if in doubt, consult our Technical Support staff.



- Always follow the Health and Safety guidance provided.
 REGULAR CLEANING IS MORE BENEFICIAL TO THE FLOORCOVERING AND MORE COST-EFFECTIVE THAN OCCASIONAL HEAVY CLEANING.
- Cleaners and detergents should be diluted as per the manufacturers' instructions. For recommended products, see the Polyflor Approved Maintenance Products sheet located within the Technical section of www.polyflor.com.
- Polysafe safety flooring ranges are compatible for use with the most commonly used alco-based hand gels and are suitable for steam cleaning on a periodic basis.
- For further clarification and advice on specific applications, consult Polyflor Customer Technical Services on +44 (0)161 767 1912, or email tech@polyflor.com.

POLYSAFETM

SAFETY FLOORING

FLOORCARE FOR
POLYSAFE STANDARD,
STRATA,
ULTIMA,
HYDRO AND
HYDRO EVOLVE.



EXPORT FAX: +44 (0)161 767 1166
E-MAIL: INFO@POLYFLOR.COM WWW.POLYFLOR.COM

James Halstend





APPROVED MAINTENANCE PRODUCTS

The companies listed have products that are approved for use with Polyflor products. For full instructions for use, and health and safety guidelines, please contact the manufacturer.

PRODUCT	DR. SCHUTZ Tel: 01296 437827 www.dr-schutz.com	BRITISH NOVA Tel: 01295 254030	PROCHEM Tel: 0208 974 1515 www.prochem.co.uk	EVANS VANODINE Tel: 01772 322200 www.evansvanodine.co.uk	ECOLAB LTD Tel: 01793 511221 www.ecolab.com	JOHNSON/ DIVERSEY Tel: 01604 783500 www.johnsondiversey.co.uk	SELDEN RESEARCH Tel: 01298 26226 www.selden.co.uk
NEUTRAL CLEANSER	Active Cleaner	Liquid 99	Prodet	High Class	Brial Action Plus	Taski 300 Carefree Stride 1000	Neutra scrubber dryer detergent
ALKALINE CLEANSER		Novaways	Alkleen	E.M.C	Gloss Express	Brillo Cleaner/ Degreaser	HD Degreaser
		Novaways Multi Purpose Sanitiser	Ultrapac Renovate	Versatile Lift	Imi Orange Imi Top	Carefree Stride 2000	Triple
			Powerclean		Powerclean	Sprint Hard Surface Cleaner	Selclen
					Imi Action Plus	Aggressor	Multi Purpose Cleaner
GERMICIDAL CLEANSER		Novacross Non food areas	Protect	Final Touch	Bioscan	Lifeguard Cleaner/ /Disinfectant Conc.	Selguard
		Novacross (unperfumed)		Esteem		Shield	Selgeine
		Food areas		Lift		Lifeguard cleaner DisinfectantTrigger	
MAINTAINER/ WASH & WAX	Floor Cleaner R1000	Novacare	Protreat	Easy Shine	Formula 71	Carefree Maintainer	Selsheen
		Novacare Lime-lite		Clean & Shine	Indur Brillant Plus	Carefree Mop & Shine	Minit Glass
				Easy Shine	Spirit Restorer	Carefree Stride 3000	Fast Lane
					Indur Top	Taski Tensol	
DRY BRIGHT EMULSION	Floor Shine	Nova Long Life	Proshine	Sustain	Isi Star	Carefree Satin	Selbrite
POLISH		Nova Long Life Satin Finish		Mexepol	Phazer Isi Star	Carefree Eturnum	Diamond Bright
				Enhance	Lodan Star	Carefree Emulsion	
					Phazer Lodan Star		
					Tuklar Medical		
SEMI BUFFABLE EMULSION	Floor Mat	Nova Supercote		Ovacryl		Carefree Buffable Floor Polish	Selexel
POLISH							Seldur
FULLY BUFFABLE EMULSION POLISH		Nova Superphalte		Easy Shine	Gemstar Laser Phazer Gem Star Laser		Selgio
POLISH	Clean & Strip	Nova Starbrite	Prostrip	Easystrip	Bendurol Maxx	Carefree Stripper	Selate
STRIPPER		Nova 2001		Sure Strip	Bendurol Top Strip	Carefree Speed Stripper	Selspeed
POWER CLEANER (Spot Cleaner)	Turbo Strip	Cleanol Lift		Lift		Sprint Spitfire	

The data presented is correct at the time of printing. However, Polyflor Ltd. reserves the right to update this information as and when necessary. For the latest information, please check our web site at www.polyflor.com

FLOORING

Polyflor Ltd, in providing this information, does not imply any equivalence between each of the different manufacturers' products, or that other products would prove unsatisfactory.

POLYFLOR LTD. PO BOX 3 RADCLIFFE NEW ROAD WHITEFIELD MANCHESTER M45 7NR UK

TEL: +44 (0)161 767 1111 UK SALES DIRECT: +44 (0)161 767 1122 UK FAX: +44 (0)161 767 1128

EXPORT FAX: +44 (0)161 767 1166 E-MAIL: INFO@POLYFLOR.COM WWW.POLYFLOR.COM

UK SAMPLE REQUESTS: +44 (0)161 767 2551

Lames Flatead**



