POLYFLOR MYSTIQUE PUR







 $2m \times 20m = 40m^2$ 300 x 300mm = 4.5m²





GENERAL PERFORMANCE EN 649 / EN ISO 10581 **ASTM F1913 ASTM F1700**



 $608 \times 608 \text{mm} = 5.17 \text{m}^2$







REACTION TO FIRE EN 13501-1 Class Bfl-S1 **ASTM E662** <450 ASTM E648 Class 1



SLIP RESISTANCE **EN 13893** Class DS **AS/NZS 4586** R9



ABRASION RESISTANCE EN 660-2 Group P EN ISO 10581 Type I



ELECTRICAL BEHAVIOUR (body voltage) EN 1815 < 2kV Classified as 'antistatic'



VOC EMISSIONS

Indoor Air Comfort GOLD Eurofins certified product AgBB VOC test: Pass

Floorscore certified (SCS Certificate Reg No: SCS-FS-02034) Finnish M1 Classification: Pass Swedish B.P.D (FLEC test): Best Class GBCA/NZGBC Green Star IEQ-VOC: Compliant



CASTOR CHAIR (continuous use) Suitable



INDENTATION RESIDUAL ASTM F970 (Modified) Static load 750psi



ENVIRONMENTALLY PREFERABLE FLOORING

Polyflor Mystique PUR achieves a BRE Global Environmental A+ Rating (Certificate No: ENP 472) in major use areas such as education and healthcare. Generic EN 15804 Environmental Product Declaration (EPD) available on request. Mystique PUR is 100% recyclable and contains 25% recycled material. Recyclable via the Recofloor scheme. Visit www.polyflor.com/environment



AGRÉMENT ASSURANCE

Polyflor Mystique PUR has been independently assessed by the British Board of Agrément and product performance is assured for at least 10 years in recommended use areas. With proper maintenance, the appearance and colour will be retained during this period.



All Polyflor commercial sheet vinyl ranges provide a continuous, impervious and hygienic flooring solution which can be confidently cleaned in accordance with recommended maintenance procedures and approved maintenance products. The implementation of an effective cleaning regime is the most important defence against infection.



Polyflor Mystique PUR features a high quality, cross-linked polyurethane reinforcement, UV cured to provide a low cost, polish-free maintenance regime for the lifetime of the flooring.



APPLICATIONS

Polyflor Mystique PUR is recommended for heavy traffic areas that require a homogeneous floorcovering that offers durability, reliability, ease of maintenance and aesthetic appeal. Ideally suited for the most demanding of areas within the Healthcare and Education sector, as well as Retail, Leisure and the Commercial environment.



Polyflor homogeneous PUR ranges are compatible for use with the most commonly used alco-based hand gels and are suitable for steam cleaning on a periodic basis. For clarification and for information regarding handling and installation, adhesives, maintenance, applications, chemical resistance and product warranty consult Polyflor Customer Technical Services on +44 (0)161 767 1912, or email tech@polyflor.com.

POLYFLOR LTD. PO BOX 3 RADCLIFFE NEW ROAD WHITEFIELD MANCHESTER M45 7NR UK UK SALES DIRECT: +44 (0)161 767 1122 UK SAMPLE REQUESTS: +44 (0)161 767 2551 EXPORT SALES DIRECT: +44 (0)161 767 1913 TECHNICAL SUPPORT: +44 (0)161 767 1912 RECEPTION: +44 (0)161 767 1111 UK FAX: +44 (0)161 767 1128 <u>James Halstend</u> EXPORT FAX: +44 (0)161 767 1166 E-MAIL: INFO@POLYFLOR.COM FLOORING WEBSITE: WWW.POLYFLOR.COM







POLYFLOR MYSTIQUE PUR

HOMOGENEOUS



PERFORMANCE AND **PROPERTIES**





In collaboration with the European Resilient Flooring Manufacturers' Institute (ERFMI), Polyflor Ltd supports sustainal construction via Environmental Product Declarations (EPDs).



