



2.0mm



2m x 20m = 40m<sup>2</sup>



2950g/m<sup>2</sup>



**GENERAL PERFORMANCE**  
EN 649 / EN ISO 10581  
ASTM F1913



**REACTION TO FIRE**  
EN 13501-1 Class Bfl-S1  
ASTM E662 <450  
ASTM E648 Class 1



**SLIP RESISTANCE**  
EN 13893 Class DS  
AS/NZS 4586 R9



**ABRASION RESISTANCE**  
EN 660-2 Group T  
EN ISO 10581 Type I



**ELECTRICAL BEHAVIOUR (body voltage)**  
EN 1815 ≤2kV  
Classified as 'antistatic'



**VOC EMISSIONS**  
Indoor Air Comfort GOLD Eurofins certified product  
AgBB VOC test: Pass  
Floorscore certified (SCS Certificate Reg No: SCS-FS-02034)  
Finnish M1 Classification: Pass  
Swedish B.P.D (FLEC test): Best Class  
GBCA/NZGBC Green Star IEQ-VOC: Compliant



**CASTOR CHAIR**  
(continuous use)  
Suitable



**INDENTATION RESIDUAL**  
ASTM F970 (Modified)  
Static load 750psi



**ENVIRONMENTALLY PREFERABLE FLOORING**  
Polyflor Pearlazzo PUR achieves a BRE Global Environmental A+ Rating (Certificate No: ENP 472) in major use areas such as education and healthcare. Generic EN 15804 Environmental Product Declaration (EPD) available on request. Pearlazzo PUR is 100% recyclable and contains 25% recycled material. Recyclable via the Recofloor scheme. Visit [www.polyflor.com/environment](http://www.polyflor.com/environment)



**AGRÉMENT ASSURANCE**  
Polyflor Pearlazzo PUR has been independently assessed by the British Board of Agrément and product performance is assured for at least 10 years in recommended use areas. With proper maintenance, the appearance and colour will be retained during this period.



**HYGIENE**  
All Polyflor commercial sheet vinyl ranges provide a continuous, impervious and hygienic flooring solution which can be confidently cleaned in accordance with recommended maintenance procedures and approved maintenance products. The implementation of an effective cleaning regime is the most important defence against infection.



Polyflor Pearlazzo PUR features a high quality, cross-linked polyurethane reinforcement, UV cured to provide a low cost, polish-free maintenance regime for the lifetime of the flooring.



**APPLICATIONS**  
Polyflor Pearlazzo PUR is recommended for heavy traffic areas that require a homogeneous floorcovering that offers durability, reliability, ease of maintenance and aesthetic appeal. Ideally suited for the most demanding of areas within the Healthcare and Education sector, as well as Retail, Leisure and the Commercial environment.



Polyflor homogeneous PUR ranges are compatible for use with the most commonly used alco-based hand gels and are suitable for steam cleaning on a periodic basis. For clarification and for information regarding handling and installation, adhesives, maintenance, applications, chemical resistance and product warranty consult Polyflor Customer Technical Services on +44 (0)161 767 1912, or email [tech@polyflor.com](mailto:tech@polyflor.com).

POLYFLOR LTD. PO BOX 3 RADCLIFFE NEW ROAD WHITEFIELD MANCHESTER M45 7NR UK  
UK SALES DIRECT: +44 (0)161 767 1122 UK SAMPLE REQUESTS: +44 (0)161 767 2551  
EXPORT SALES DIRECT: +44 (0)161 767 1913 TECHNICAL SUPPORT: +44 (0)161 767 1912  
RECEPTION: +44 (0)161 767 1111 UK FAX: +44 (0)161 767 1128  
EXPORT FAX: +44 (0)161 767 1166 E-MAIL: [INFO@POLYFLOR.COM](mailto:INFO@POLYFLOR.COM)  
WEBSITE: [WWW.POLYFLOR.COM](http://WWW.POLYFLOR.COM)

*James Halcroft*  
FLOORING



2011



# POLYFLOR PEARLAZZO PUR

HOMOGENEOUS



## PERFORMANCE AND PROPERTIES



In collaboration with the European Resilient Flooring Manufacturers' Institute (ERFMI), Polyflor Ltd supports sustainable construction via Environmental Product Declarations (EPDs).

