

ACOUSTIX GALLERY FX

- Heterogeneous vinyl sheet for residential and heavy commercial areas
- Provides high impact sound reduction
- Polyurethane reinforcement for a low cost, lifetime, polish free maintenance regime

SPECIFICATION



3.5mm



0.5mm



2m x 20m = 40m²



2550g/m²



GENERAL PERFORMANCE
EN 651



ACOUSTIC IMPACT SOUND REDUCTION
EN ISO 140-8 ≥19dB
EN ISO 10140-3 ≥19dB



SLIP RESISTANCE
EN 13893 Class DS (dry condition)
DIN 51130 R10
For safety flooring with sustainable wet slip resistance, refer to the Polysafe ranges.



REACTION TO FIRE
EN 13501-1 Class Bfl-S1



RESISTANCE TO CHEMICALS
EN 423 (ASTM F 1303-99)
Excellent chemical resistance



LIGHT FASTNESS
ISO 105-B02 (Method 3) ≥6



ABRASION RESISTANCE
EN 649 Group T
EN ISO 10582 Type 1



INDENTATION - RESIDUAL
EN 433 <0.2mm



DIMENSIONAL STABILITY
EN 434 <0.40%



FLEXIBILITY
EN 435 (Method A) Pass
20mm Ø



THERMAL RESISTANCE
Suitable for underfloor heating
ISO 8302 0.0525 m² K/W



VOC EMISSIONS
Indoor Air Comfort GOLD Approved
AgBB very low emissions
FloorScore certified product



HYGIENE
This product has been independently tested and results demonstrate that it inhibits the growth of MRSA on the flooring. An effective cleaning regime is however, the most important defence against infection.



ELECTRICAL BEHAVIOUR (body voltage)
EN1815 This product does not accumulate static charges above 2kV and is classified as 'antistatic'. For specialist applications where there is a requirement to dissipate the electrostatic charge, see the Polyflor ESD product ranges.



ENVIRONMENTALLY PREFERABLE FLOORING
Polyflor Acoustix Gallery fx PUR achieves BRE Global A+ rating (ENP 415) in the green guide to specification. It is 100% recyclable. Recyclable via the Recofloor scheme. Visit www.polyflor.com/environment



Polyflor Acoustix Gallery fx PUR features a high quality, cross-linked polyurethane reinforcement, UV cured to provide a low cost, polish-free maintenance regime for the lifetime of the flooring.



APPLICATIONS
Polyflor Acoustix Gallery fx PUR is suitable for use in residential or commercial buildings where sound insulation is an important feature, for example apartments, communal areas, student accommodation etc.



For information regarding handling and installation, adhesives, maintenance, applications and chemical resistance, consult Polyflor Customer Technical Services on +44 (0)161 767 1912, or email tech@polyflor.com.

ACOUSTIX GALLERY FX PUR MAY INCLUDE KNOTS OR MARKINGS AS PART OF THE DESIGN.

For best results, all none-wood effect designs must be reverse laid.

POLYFLOR LTD. PO BOX 3 RADCLIFFE NEW ROAD WHITEFIELD MANCHESTER M45 7NR UK
UK SALES DIRECT: +44 (0)161 767 1122 UK SAMPLE REQUESTS: +44 (0)161 767 2551
EXPORT SALES DIRECT: +44 (0)161 767 1913 TECHNICAL SUPPORT: +44 (0)161 767 1912
RECEPTION: +44 (0)161 767 1111 UK FAX: +44 (0)161 767 1128
EXPORT FAX: +44 (0)161 767 1166
E-MAIL: INFO@POLYFLOR.COM WWW.POLYFLOR.COM

James Hatfield
FLOORING



2011



Acoustix Gallery fx™


Acoustic vinyl flooring



PERFORMANCE AND PROPERTIES



Refer to BRE Global ratings on www.greenbooklive.com



POLYFLOR™
COVERING THE WORLD