

## POLYSAFE ULTIMA

- BRE Global A+ Rated Product (Certificate No: ENP 336)
- Heavy-duty safety flooring with enhanced slip resistance
- Surface roughness Rz  $\geq 70\mu\text{m}$  for use in commercial kitchens with risk of high viscosity contamination
- Coloured quartz, aluminium oxide and silicon carbide particles incorporated through the vinyl to improve traction and safety underfoot

## SPECIFICATION



2.5mm

2m x 20m = 40m<sup>2</sup>3000g/m<sup>2</sup>

## GENERAL PERFORMANCE

EN 13845  
ASTM F1303

## REACTION TO FIRE

EN 13501-1 Class Bfl-S1 { EN ISO 9239-1  $\geq 8\text{kw/m}^2$   
EN ISO 11925-2 Pass

ASTM E648 Class 1



## ENHANCED SLIP

Sustainable wet slip resistance\* AS/NZS 4586 R11

EN 13845 ESf

RRL Pendulum Test  $\geq 40$  (wet test - 4S Rubber/Slider 96)Surface roughness Rz  $\geq 70\mu\text{m}$  (Typical result)

The slip resistance across all Polysafe products is assured throughout the guaranteed life of the product, with strict adherence to HSE Guidelines.



## ABRASION RESISTANCE

EN 13845 50,000 cycles  
EN 649 Group T

## VOC EMISSIONS

AgBB VOC test :  
Cert No: Z-156 603-523  
Florescore certified  
Cert No: SCS-FS-02034

## AGRÉMENT ASSURANCE

Polysafe Ultima has been independently assessed by the British Board of Agrément and product performance is assured for at least 10 years in recommended use areas. With proper maintenance, the appearance, colour and slip resistance will be retained during this period.



## ENVIRONMENTALLY PREFERABLE FLOORING

Polysafe Ultima achieves a BRE Global Environmental A+ Rating (Certificate No: ENP 336) in major use areas such as education and healthcare. Polysafe Ultima is 100% recyclable and contains recycled material. A full Environmental Report detailing Polyflor's achievements in areas such as recycling, energy reduction and waste avoidance can be found at [www.polyflor.com/environment](http://www.polyflor.com/environment)

## ELECTRICAL BEHAVIOUR

(body voltage)

EN 1815  $\leq 2\text{kV}$   
Classified as 'antistatic'

## RESISTANCE TO CHEMICALS

Good resistance to dilute acids and alkalis. Chemical resistance charts available on request.



## HYGIENE

Contains antimicrobial agents. Independently tested - inhibits growth of MRSA on flooring. Effective maintenance is most important defence against infection.



## APPLICATIONS

Polysafe Ultima is specially designed to be used in busy commercial areas where enhanced slip resistance is of paramount importance. The range is particularly suitable in commercial kitchens and food preparation areas where there is a requirement to serve over 100 meals per day and a need for the floor to perform under the demands of heavy footfall and high viscosity contaminants such as oil and grease. For continually wet areas please refer to our Polysafe Hydro range. As with all Polysafe products, Polysafe Ultima should not have a polish applied.

Polysafe safety flooring ranges are compatible for use with the most commonly used alco-based hand gels and are suitable for steam cleaning on a periodic basis. For clarification and for information regarding handling and installation, adhesives, maintenance, applications and chemical resistance, consult Polyflor Customer Technical Services on +44 (0)161 767 1912, or email [tech@polyflor.com](mailto:tech@polyflor.com). At the date of issue the data presented is correct. However, Polyflor Ltd. reserves the right to make changes which do not adversely affect performance or quality.  
\* For clarification regarding slip resistance, consult Polyflor.

POLYFLOR LTD. PO BOX 3 RADCLIFFE NEW ROAD WHITEFIELD MANCHESTER M45 7NR UK  
 UK SALES DIRECT: +44 (0)161 767 1122 UK SAMPLE REQUESTS: +44 (0)161 767 2551  
 EXPORT SALES DIRECT: +44 (0)161 767 1913 TECHNICAL SUPPORT: +44 (0)161 767 1912  
 RECEPTION: +44 (0)161 767 1111 UK FAX: +44 (0)161 767 1128  
 EXPORT FAX: +44 (0)161 767 1166  
 E-MAIL: [INFO@POLYFLOR.COM](mailto:INFO@POLYFLOR.COM) [WWW.POLYFLOR.COM](http://WWW.POLYFLOR.COM)

*James Halstead*  
 FLOORING




POLYFLOR  
**POLYSAFE™**  
**ULTIMA**

## SAFETY FLOORING

## PERFORMANCE AND PROPERTIES



Refer to BRE Global ratings  
 on [www.greenbooklive.com](http://www.greenbooklive.com)



EN 13845

**POLYFLOR™**  
 COVERING THE WORLD