

POLYFLOR PRESTIGE PUR



2.0mm



2m x 20m = 40m²



300 x 300mm = 4.5m²
608 x 608mm = 5.17m²



3030g/m²



GENERAL PERFORMANCE

EN 649 / EN ISO 10581

ASTM F1913

ASTM F1700



REACTION TO FIRE

EN 13501-1 Class Bfl-s1

ASTM E662 <450

ASTM E648 Class 1



SLIP RESISTANCE

EN 13893 Class DS

AS/NZS 4586 R9



ABRASION RESISTANCE

EN 660-2 Group P

EN ISO 10581 Type I



ELECTRICAL BEHAVIOUR

(body voltage)

EN 1815 <2kV

Classified as 'antistatic'



VOC EMISSIONS

Indoor Air Comfort GOLD Eurofins certified product

AgBB VOC test: Pass

Floorscore certified (SCS Certificate Reg No: SCS-FS-02034)

Finnish M1 Classification: Pass

Swedish B.P.D (FLEC test): Best Class

GBCA/NZGBC Green Star IEQ-VOC: Compliant



CASTOR CHAIR

(continuous use)

Suitable



INDENTATION RESIDUAL

ASTM F970 (Modified)

Static load 750psi



ENVIRONMENTALLY PREFERABLE FLOORING

Polyflor Prestige PUR achieves a BRE Global Environmental A+ Rating (Certificate No: ENP 472) in major use areas such as education and healthcare.

Generic EN 15804 Environmental Product Declaration (EPD) available on request.

Prestige PUR is 100% recyclable and contains 25% recycled material. Recyclable via the Recofloor scheme.

Visit www.polyflor.com/environment



AGRÉMENT ASSURANCE

Polyflor Prestige PUR has been independently assessed by the British Board of Agrément and product performance is assured for at least 10 years in recommended use areas. With proper maintenance, the appearance and colour will be retained during this period.



HYGIENE

All Polyflor commercial sheet vinyl ranges provide a continuous, impervious and hygienic flooring solution which can be confidently cleaned in accordance with recommended maintenance procedures and approved maintenance products. The implementation of an effective cleaning regime is the most important defence against infection.



Polyflor Prestige PUR features a high quality, cross-linked polyurethane reinforcement, UV cured to provide a low cost, polish-free maintenance regime for the lifetime of the flooring.



APPLICATIONS

Polyflor Prestige PUR is recommended for heavy traffic areas that require a homogeneous floorcovering that offers durability, reliability, ease of maintenance and aesthetic appeal. Ideally suited for the most demanding of areas within the Healthcare and Education sector, as well as Retail, Leisure and the Commercial environment.



Polyflor homogeneous PUR ranges are compatible for use with the most commonly used alco-based hand gels and are suitable for steam cleaning on a periodic basis. For clarification and for information regarding handling and installation, adhesives, maintenance, applications, chemical resistance and product warranty consult Polyflor Customer Technical Services on +44 (0)161 767 1912, or email tech@polyflor.com.



POLYFLOR
PRESTIGE PUR
HOMOGENEOUS




PERFORMANCE AND
PROPERTIES



Refer to BRE Global ratings on www.greenbooklive.com



In collaboration with the European Resilient Flooring Manufacturers' Institute (ERFMI), Polyflor Ltd supports sustainable construction via Environmental Product Declarations (EPDs).



POLYFLOR LTD. PO BOX 3 RADCLIFFE NEW ROAD WHITEFIELD MANCHESTER M45 7NR UK
UK SALES DIRECT: +44 (0)161 767 1122 UK SAMPLE REQUESTS: +44 (0)161 767 2551
EXPORT SALES DIRECT: +44 (0)161 767 1913 TECHNICAL SUPPORT: +44 (0)161 767 1912
RECEPTION: +44 (0)161 767 1111 UK FAX: +44 (0)161 767 1128
EXPORT FAX: +44 (0)161 767 1166 E-MAIL: INFO@POLYFLOR.COM
WEBSITE: WWW.POLYFLOR.COM

James Hulet
FLOORING



2011

October 2013

