

SAARFLOOR NOPPE STUD TILE

- Heavy contract, synthetic rubber floor tiles
- Resilience and comfort underfoot
- Low profile studded surface

SPECIFICATION



3.0mm
4.0mm



20 @ 500 x 500mm = 5m²
16 @ 500 x 500mm = 4m²



4200g/m²
5600g/m²



GENERAL PERFORMANCE

EN 12199

3mm



4mm



REACTION TO FIRE

EN 13501-1 Class Cfl-S1

EN ISO 9239-1 ≥4.5kw/m²

EN ISO 11925-2 Pass



CIGARETTE RESISTANCE

EN 1399

Method A Rating >4

Method B Rating >3



SLIP RESISTANCE

EN 13893 Class DS



ACOUSTICAL IMPACT SOUND REDUCTION

EN ISO 140-8

Rubber floors make a beneficial contribution to impact sound reduction.



APPLICATIONS

SaarFloor-Systems Noppe Stud Tile is suitable for very heavy commercial use in areas of high public circulation such as shopping malls, train stations, airports, department stores, hospitals, educational establishments and other public buildings.

Prolonged exposure to oil, grease and fats causes deterioration.

SaarFloor-Systems Noppe Stud Tile is suitable for areas where spillage is infrequent, but not garage workshops or food preparation areas.

Under very wet conditions slip resistance is impaired.

SaarFloor-Systems Noppe Stud Tile is not recommended for exterior use or swimming pool surrounds.




For information regarding handling and installation, adhesives, maintenance, applications and chemical resistance, consult Polyflor.



SaarFloor
Systems

NOPPE STUD TILE

PERFORMANCE AND PROPERTIES



POLYFLOR LTD. PO BOX 3 RADCLIFFE NEW ROAD WHITEFIELD MANCHESTER M45 7NR UK
TEL: +44 (0)161 767 1111 UK SALES DIRECT: +44 (0)161 767 1122 UK FAX: +44 (0)161 767 1128
EXPORT FAX: +44 (0)161 767 1166 E-MAIL: INFO@POLYFLOR.COM WWW.POLYFLOR.COM
UK SAMPLE REQUESTS: +44 (0)161 767 2551

James Halstead
FLOORING



January 2007

POLYFLOR
COVERING THE WORLD