

POLYSAFE CORONA PUR



2.0mm



2m x 20m = 40m²



2400g/m²



GENERAL PERFORMANCE

EN 13845
ASTM F1303



REACTION TO FIRE
EN 13501-1 Class Bfl-S1
ASTM E648 Class 1



ABRASION RESISTANCE
EN 13845 50,000 cycles
EN 649 Group T



ENHANCED SLIP
Sustainable wet slip resistance* AS/NZS 4586 R10
EN 13845 ESf
RRL Pendulum Test ≥36 (wet test - 4S Rubber/Slider 96)
Surface roughness Rz ≥20µm
The slip resistance across all Polysafe products is assured throughout the guaranteed life of the product, with strict adherence to HSE Guidelines.



ENVIRONMENTALLY PREFERABLE FLOORING
Polysafe Corona PUR achieves BRE Global A+ rating (ENP 472) in the Green Guide to Specification in use areas such as education and healthcare and is GreenTag LCARate certified with GreenRate level A. Environmental Product Declaration EN 15804 EPD is available on request. It is 100% recyclable and contains recycled material. Recyclable via the Recofloor scheme. Visit www.polyflor.com/environment



VOC EMISSIONS
AgBB/DIBT : Pass
FloorScore certified
GBCA/NZGBC Green Star EQ-VOC: Compliant



ELECTRICAL BEHAVIOUR (body voltage)
EN 1815 ≤2kV
Classified as 'antistatic'



RESISTANCE TO CHEMICALS
Good resistance to dilute acids and alkalis. Chemical resistance charts available on request.



AGRÉMENT ASSURANCE
Polysafe Corona PUR has been independently assessed by the British Board of Agrément and product performance is assured for at least 10 years in recommended use areas. With proper maintenance, the appearance, colour and slip resistance will be retained during this period.



HYGIENE
All Polyflor commercial sheet vinyl ranges provide a continuous, impervious and hygienic flooring solution which can be confidently cleaned in accordance with recommended maintenance procedures and approved maintenance products. The implementation of an effective cleaning regime is the most important defence against infection.



Polysafe Corona incorporates Suprathec PUR, engineered to provide the best in colour, aesthetics and flexibility. This high quality, cross-linked polyurethane reinforcement is UV cured to provide superior cleaning benefits, life cycle maintenance savings and optimum appearance retention. As with all Polysafe products, Corona PUR should not have polish applied.



APPLICATIONS
Polysafe Corona PUR is ideal for use where enhanced slip resistance is required in areas that are subject to contaminant spillages and are hygiene critical locations e.g. food preparation areas, kitchens and bar serveries. The advantages in cleanability make Polysafe Corona PUR suitable for general areas e.g. supermarkets, clinics, laundry and sluice rooms, washrooms, WCs, laboratories, classrooms and many institutional applications. For continually wet areas please refer to our Polysafe Hydro or Hydro Evolve ranges.



Polysafe safety flooring ranges are compatible for use with the most commonly used alco-based hand gels and are suitable for steam cleaning on a periodic basis. For clarification and for information regarding handling and installation, adhesives, maintenance, applications and chemical resistance, consult Polyflor Customer Technical Services on +44 (0)161 767 1912, or email tech@polyflor.com. At the date of issue the data presented is correct. However, Polyflor Ltd. reserves the right to make changes which do not adversely affect performance or quality.
* For clarification regarding slip resistance, consult Polyflor.




POLYFLOR
**POLYSAFE™
CORONA PUR**



**PERFORMANCE AND
PROPERTIES**



In collaboration with the European Resilient Flooring Manufacturers' Institute (ERFMI), Polyflor Ltd supports sustainable construction via Environmental Product Declarations (EPDs).



POLYFLOR LTD. PO BOX 3 RADCLIFFE NEW ROAD WHITEFIELD MANCHESTER M45 7NR UK
UK SALES DIRECT: +44 (0)161 767 1122 UK SAMPLE REQUESTS: +44 (0)161 767 2551
EXPORT SALES DIRECT: +44 (0)161 767 1913 TECHNICAL SUPPORT: +44 (0)161 767 1912
RECEPTION: +44 (0)161 767 1111 UK FAX: +44 (0)161 767 1128
EXPORT FAX: +44 (0)161 767 1166
E-MAIL: INFO@POLYFLOR.COM WWW.POLYFLOR.COM

James Halstead
FLOORING



2011

