

POLYSAFE APEX



2.5mm



2m x 20m = 40m²



3150g/m²



GENERAL PERFORMANCE
EN 13845



REACTION TO FIRE
EN 13501-1 Class Bfl-S1



ABRASION RESISTANCE
EN 13845 50,000 cycles
EN 649 Group T



ENHANCED SLIP
Sustainable wet slip resistance* DIN 51130 R12
EN 13845 ESf
AS/NZS 4586 R12

RRL Pendulum Test ≥45 (wet test - 4S Rubber/Slider 96)
Surface roughness Rz ≥70µm (Typical result)
The slip resistance across all Polysafe products is assured throughout the guaranteed life of the product, with strict adherence to HSE Guidelines.



VOC EMISSIONS
AgBB/DIBT: Pass
GBCA/NZGBC Green Star IEQ-VOC: Compliant



HYGIENE
All Polyflor commercial sheet vinyl ranges provide a continuous, impervious and hygienic flooring solution which can be confidently cleaned in accordance with recommended maintenance procedures and approved maintenance products. The implementation of an effective cleaning regime is the most important defence against infection.



ENVIRONMENTALLY PREFERABLE FLOORING
Polysafe Apex achieves BRE Global Environmental Generic A+ rating in major use areas such as education and healthcare and is GreenTag LCA Rate certified with GreenRate level A. Generic Environmental Product Declaration EN 15804 EPD is available on request. It is 100% recyclable and contains recycled material. Recyclable via the Recofloor scheme. Visit www.polyflor.com/environment



ELECTRICAL BEHAVIOUR (body voltage)
EN 1815 ≤2kV
Classified as 'antistatic'



RESISTANCE TO CHEMICALS
Good resistance to dilute acids and alkalis. Chemical resistance charts available on request.



APPLICATIONS
Polysafe Apex is specially designed with enhanced levels of slip resistance for use in the more extreme and intensive food production and processing areas where there are risks of high viscosity contaminants. Particularly suitable in busy kitchen environments whether commercial, gourmet or food preparation areas where over 100 meals are served daily and where the floor is subjected to everyday spillages such as cooking oil, margarine and grease. Examples include kitchens within hospitals, schools, hotels, restaurants and fast food establishments. As with all Polysafe products, Polysafe Apex should not have a polish applied.



Polysafe safety flooring ranges are compatible for use with the most commonly used alco-based hand gels and are suitable for steam cleaning on a periodic basis. For clarification and for information regarding handling and installation, adhesives, maintenance, applications and chemical resistance, consult Polyflor Customer Technical Services on +44 (0)161 767 1912, or email tech@polyflor.com. At the date of issue the data presented is correct. However, Polyflor Ltd. reserves the right to make changes which do not adversely affect performance or quality.
* For clarification regarding slip resistance, consult Polyflor.

POLYFLOR LTD. POBOX 3 RADCLIFFE NEW ROAD WHITEFIELD MANCHESTER M45 7NR UK
UK SALES DIRECT: +44 (0)161 767 1122 UK SAMPLE REQUESTS: +44 (0)161 767 2551
EXPORT SALES DIRECT: +44 (0)161 767 1913 TECHNICAL SUPPORT: +44 (0)161 767 1912
RECEPTION: +44 (0)161 767 1111 UK FAX: +44 (0)161 767 1128
EXPORT FAX: +44 (0)161 767 1166
E-MAIL: INFO@POLYFLOR.COM WWW.POLYFLOR.COM

James Holstead
FLOORING



2011



POLYFLOR
POLYSAFE™
APEX

SAFETY FLOORING

PERFORMANCE AND PROPERTIES



Refer to the BRE Green Guide for more details (www.thegreenguide.org.uk)



In collaboration with the European Resilient Flooring Manufacturers' Institute (ERFMI), Polyflor Ltd supports sustainable construction via Environmental Product Declarations (EPDs).

