

FOREST FX

- Developed from authentic reproductions of wood flooring
- Collection of 14 wood designs
- Polyurethane reinforced to aid ongoing maintenance

SPECIFICATION



2.0mm



0.70mm



2m x 20m = 40m²



2700g/m²



GENERAL PERFORMANCE EN 649



REACTION TO FIRE EN 13501-1 Class Bfl-s1



SLIP RESISTANCE EN 13893 Class DS (dry condition) AS/NZS 4586 R10

For safety flooring with sustainable wet slip resistance, refer to the Polysafe ranges.



RESISTANCE TO CHEMICALS EN 423 (ASTM F 1303-99) Excellent chemical resistance



LIGHT FASTNESS ISO 105-B02 (Method3) ≥6



ABRASION RESISTANCE EN 649: 1996 Group T



INDENTATION - RESIDUAL EN 433 <0.10mm



DIMENSIONAL STABILITY EN 434 <0.40%



FLEXIBILITY EN 435 Method A Pass 20mm Ø



CASTOR CHAIR (continuous use) EN 425 Pass Suitable for castor chairs



THERMAL CONDUCTIVITY Suitable for underfloor heating (Max 27°C)



HYGIENE
This product has been independently tested and results demonstrate that it inhibits the growth of MRSA. An effective cleaning regime is however, the most important defence against infection.



ELECTRICAL BEHAVIOUR (body voltage)
EN1815 This product does not accumulate static charges above 2kV and is classified as 'antistatic'. For specialist applications where there is a requirement to dissipate the electrostatic charge, see the Polyflor ESD product ranges.



ENVIRONMENTALLY PREFERABLE FLOORING
Polyflor Forest fx PUR achieves a BRE Global Environmental A+ Rating (Certificate No: ENP 415) in major use areas such as education and healthcare. Polyflor Forest fx PUR is 100% recyclable. A full Environmental Report detailing Polyflor's achievements in areas such as recycling, energy reduction and waste avoidance can be found at www.polyflor.com/environment



Polyflor Forest fx PUR features a high quality, cross-linked polyurethane reinforcement, UV cured to provide a low cost, polish-free maintenance regime for the lifetime of the flooring.



APPLICATIONS
Polyflor Forest fx PUR is recommended for heavy traffic areas that require a hardwearing floorcovering which is attractive, modern and easy to maintain. Such areas include banking halls, retail showrooms, department stores, hotels, restaurants, leisure centres, universities, hospitals, health clinics, libraries, commercial offices and public reception areas.



For information regarding handling and installation, adhesives, maintenance, applications and chemical resistance, consult Polyflor Customer Technical Services on +44 (0)161 767 1912, or email tech@polyflor.com.

VARIATION IN COLOUR AND DESIGN IS A FEATURE OF THIS PRODUCT INTENDED TO ENHANCE THE NATURAL APPEARANCE OF THE FLOOR.

POLYFLOR LTD. PO BOX 3 RADCLIFFE NEW ROAD WHITEFIELD MANCHESTER M45 7NR UK
UK SALES DIRECT: +44 (0)161 767 1122 UK SAMPLE REQUESTS: +44 (0)161 767 2551
EXPORT SALES DIRECT: +44 (0)161 767 1913 TECHNICAL SUPPORT: +44 (0)161 767 1912
RECEPTION: +44 (0)161 767 1111 UK FAX: +44 (0)161 767 1128
EXPORT FAX: +44 (0)161 767 1166 E-MAIL: INFO@POLYFLOR.COM
WEBSITE: WWW.POLYFLOR.COM

James Halstead
FLOORING



2011




Forest fx™

Wood effect sheet vinyl flooring



PERFORMANCE AND PROPERTIES



POLYFLOR™
COVERING THE WORLD