

POLYSAFE WOOD FX PUR

- Reinforced with Polysafe PUR for optimum appearance retention
- Up to 60% life cycle maintenance cost saving compared to untreated safety floors
- Fully HSE compliant
- BRE Global A+ Rated Product (Certificate No: ENP 415)

SPECIFICATION



2.0mm



0.70mm



2m x 20m = 40m²



3000g/m²



GENERAL PERFORMANCE

EN 13845
ASTM F1303



REACTION TO FIRE
EN 13501-1 Class Bfl-S1
ASTM E648 Class 1



ENHANCED SLIP

Sustainable wet slip resistance* AS/NZS 4586 R10
EN 13845 ESf

RRL Pendulum Test ≥ 36 (wet test - 4S Rubber/Slider 96)
Surface roughness Rz $\geq 20\mu\text{m}$

The slip resistance across all Polysafe products is assured throughout the guaranteed life of the product, with strict adherence to HSE Guidelines.



ABRASION RESISTANCE
EN 13845 50,000 cycles
EN 649 Group T



VOC EMISSIONS
AgBB VOC test: Pass
(Low Result)



ENVIRONMENTALLY PREFERABLE FLOORING

Polysafe Wood FX PUR achieves BRE Global A+ rating (ENP 415) in the green guide to specification and is certified GreenTag Gold. It is 100% recyclable. Recyclable via the Recofloor scheme. Visit www.polyflor.com/environment



ELECTRICAL BEHAVIOUR
(body voltage)
EN 1815 $\leq 2\text{kV}$
Classified as 'antistatic'



RESISTANCE TO CHEMICALS
Good resistance to dilute acids and alkalis. Chemical resistance charts available on request.



AGRÉMENT ASSURANCE
Independently assessed by the BBA and awarded a 10 year product performance assurance in recommended use areas.



HYGIENE
Contains antimicrobial agents. Independently tested - inhibits growth of MRSA on flooring. Effective maintenance is the most important defence against infection.



Polysafe Wood FX PUR features a high quality, cross-linked polyurethane reinforcement, UV cured to provide superior cleaning benefits, life cycle maintenance savings and optimum appearance retention. As with all Polysafe products, Polysafe Wood FX PUR should not have a polish applied.



APPLICATIONS

Polysafe Wood FX PUR is ideal for use in busy front of house public areas which are normally dry but where there is a risk that water spillage can occur, making slip resistance an important consideration. Typical areas include corridors and circulation areas, receptions, hospital wards, classrooms, shops and cafes as well as social housing applications and normal back of house safety areas. This includes washrooms, WCs, bar serveries and changing rooms. For continually wet areas please refer to our Polysafe Hydro or Hydro Evolve ranges.



Polysafe safety flooring ranges are compatible for use with the most commonly used alco-based hand gels and are suitable for steam cleaning on a periodic basis. For clarification and for information regarding handling and installation, adhesives, maintenance, applications and chemical resistance, consult Polyflor Customer Technical Services on +44 (0)161 767 1912, or email tech@polyflor.com. At the date of issue the data presented is correct. However, Polyflor Ltd. reserves the right to make changes which do not adversely affect performance or quality.

* For clarification regarding slip resistance, consult Polyflor.

POLYFLOR LTD. PO BOX 3 RADCLIFFE NEW ROAD WHITEFIELD MANCHESTER M45 7NR UK
UK SALES DIRECT: +44 (0)161 767 1122 UK SAMPLE REQUESTS: +44 (0)161 767 2551
EXPORT SALES DIRECT: +44 (0)161 767 1913 TECHNICAL SUPPORT: +44 (0)161 767 1912
RECEPTION: +44 (0)161 767 1111 UK FAX: +44 (0)161 767 1128
EXPORT FAX: +44 (0)161 767 1166
E-MAIL: INFO@POLYFLOR.COM WWW.POLYFLOR.COM

James Salter
FLOORING



POLYFLOR


POLYSAFE™
Woodfx



PERFORMANCE AND
PROPERTIES

A+BRE
ENP 415
ENVIRONMENTAL
RATING

Refer to BRE Global ratings on
www.greenbooklive.com



POLYFLOR™
COVERING THE WORLD