

POLYFLOR 2000 PUR



2.0mm
2.5mm



2m x 20m = 40m²
2m x 15m = 30m²



300 x 300mm
4.5m²
3.6m²



608 x 608mm
5.17m²
-



3550g/m²
4552g/m²



GENERAL PERFORMANCE
EN 649 / EN ISO 10581
ASTM F1913
ASTM F1700



REACTION TO FIRE
EN 13501-1 Class Bfl-S1
ASTM E662[†] <450
ASTM E648[†] Class 1



SLIP RESISTANCE
EN 13893 Class DS
AS/NZS 4586 R9



ABRASION RESISTANCE
EN 660-2 Group M
EN ISO 10581 Type II



ELECTRICAL BEHAVIOUR
(body voltage)
EN 1815 ≤2kV
Classified as 'antistatic'



MARITIME USAGE
American Bureau of Shipping[†]
US Coast Guard Approved
Marine Equipment Directive[†]
96/98/EC
SOLAS 74



AGRÉMENT ASSURANCE
Independently assessed by the
BBA and awarded a 10 year
product performance assurance
in recommended use areas.



CASTOR CHAIR
(continuous use)
Suitable



INDENTATION RESIDUAL
ASTM F970 (Modified)
Static load 750psi



RESPONSIBLE SOURCING
BES 6001 Very Good



VOC EMISSIONS
Indoor Air Comfort GOLD Eurofins certified product
AgBB VOC test: Pass
Floorscore certified (SCS Certificate Reg No: SCS-FS-02034)
Finnish M1 Classification:[†] Pass
Swedish B.P.D (FLEC test):[†] Best Class
GBCA/NZGBC Green Star IEQ-VOC:[†] Compliant



HYGIENE
All Polyflor commercial sheet vinyl ranges provide a continuous, impervious and hygienic flooring solution which can be confidently cleaned in accordance with recommended maintenance procedures and approved maintenance products. The implementation of an effective cleaning regime is the most important defence against infection.



ENVIRONMENTALLY PREFERABLE FLOORING
Polyflor 2000 PUR achieves a BRE Global Environmental A+ Rating (Certificate No: ENP 472) in major use areas such as education and healthcare and is Green Tag LCA Rate certified with GreenRate level A - Gold Plus. Generic EN 15804 Environmental Product Declaration (EPD) available on request. 2000 PUR is 100% recyclable and contains 25% recycled material. Recyclable via the Recofloor scheme. Visit www.polyflor.com/environment



Polyflor 2000 PUR features a high quality, cross-linked polyurethane reinforcement, UV cured to provide a low cost, polish-free maintenance regime for the lifetime of the flooring.



APPLICATIONS
Polyflor 2000 PUR is especially recommended for hospitals, schools, offices, supermarkets and institutional buildings, where an easy to maintain, hardwearing floorcovering with an attractive, modern appearance is required.



Polyflor homogeneous PUR ranges are compatible for use with the most commonly used alco-based hand gels and are suitable for steam cleaning on a periodic basis. For clarification and for information regarding handling and installation, adhesives, maintenance, applications, chemical resistance and product warranty consult Polyflor Customer Technical Services on +44 (0)161 767 1912, or email tech@polyflor.com.

†±2.0mm

POLYFLOR LTD. PO BOX 3 RADCLIFFE NEW ROAD WHITEFIELD MANCHESTER M45 7NR UK
UK SALES DIRECT: +44 (0)161 767 1122 UK SAMPLE REQUESTS: +44 (0)161 767 2551
EXPORT SALES DIRECT: +44 (0)161 767 1913 TECHNICAL SUPPORT: +44 (0)161 767 1912
RECEPTION: +44 (0)161 767 1111 UK FAX: +44 (0)161 767 1128
EXPORT FAX: +44 (0)161 767 1166 E-MAIL: INFO@POLYFLOR.COM
WEBSITE: WWW.POLYFLOR.COM

James Halstead
FLOORING



2011



POLYFLOR
2000 PUR
HOMOGENEOUS



PERFORMANCE AND
PROPERTIES



In collaboration with the European Resilient Flooring Manufacturers' Institute (ERFMI), Polyflor Ltd supports sustainable construction via Environmental Product Declarations (EPDs).

