

## SAARFLOOR DIAMANT

- Heavy contract, synthetic rubber sheet floorcovering
- Multicoloured chip decoration
- Embossed surface finish

### SPECIFICATION



2.0mm



1.90m x 15m = 28.5m<sup>2</sup>



3200g/m<sup>2</sup>



#### GENERAL PERFORMANCE

EN 1817



#### REACTION TO FIRE

EN 13501-1 Class Bfl-S1

EN ISO 9239-1 >8kw/m<sup>2</sup>

EN ISO 11925-2 Pass



#### CIGARETTE RESISTANCE

EN 1399 Method A Rating >4

Method B Rating >3



#### SLIP RESISTANCE

EN 13893 Class DS



#### ACOUSTICAL IMPACT SOUND REDUCTION

EN ISO 140-8

Rubber floors make a beneficial contribution to impact sound reduction.



#### APPLICATIONS

SaarFloor-Systems Diamant is especially recommended for public, institutional and commercial buildings where ease of maintenance and long life under heavy traffic are required.

Prolonged exposure to oil, grease and fats causes deterioration.

SaarFloor-Systems Diamant is suitable for areas where spillage is infrequent, but not garage workshops or food preparation areas.

SaarFloor-Systems Diamant is not recommended for exterior use or swimming pool surrounds.



For information regarding handling and installation, adhesives, maintenance, applications and chemical resistance, consult Polyflor.



POLYFLOR LTD. PO BOX 3 RADCLIFFE NEW ROAD WHITEFIELD MANCHESTER M45 7NR UK  
 TEL: +44 (0)161 767 1111 UK SALES DIRECT: +44 (0)161 767 1122 UK FAX: +44 (0)161 767 1128  
 EXPORT FAX: +44 (0)161 767 1166 E-MAIL: INFO@POLYFLOR.COM WWW.POLYFLOR.COM  
 UK SAMPLE REQUESTS: +44 (0)161 767 2551


*James Halstead*  
 FLOORING



SaarFloor  
 Systems

DIAMANT

PERFORMANCE AND  
 PROPERTIES



**POLYFLOR**  
 COVERING THE WORLD