

# Arte della Ceramica




## BOUNCEBACKABILITY

The resilient foam backing ensures 'bouncebackability' and appearance retention.









## GREATER DURABILITY AND EASY CLEANING

The protective top coat reduces scuffing and staining, making your floor easy to clean.










## 10 YEARS GUARANTEE

## PRODUCT INFORMATION

|                   | NORM   | SYMBOL  | ARTE DELLA CERAMICA |
|-------------------|--------|---|---------------------|
| Classification    | EN 685 |    | 23                  |
| Total thickness   | EN 428 |   | 2.50mm              |
| Wearlayer         | EN 429 |  | 0.25mm              |
| Width             | EN 426 |  | 4m                  |
| Standard length   | EN 426 |  | 30m                 |
| Total roll weight | -      |  | 180 kg / 240 kg     |

## TECHNICAL INFORMATION

|                       | NORM          | SYMBOL  | ARTE DELLA CERAMICA                             |
|-----------------------|---------------|---|---|
| Light stability       | ISO 105 - B02 |  | ≥6  |
| Dimensional stability | EN 434        |  | ≤ 0,40%   |
| Impact sound          | EN ISO 717/2  |  | ΔLw 20dB  |
| Underfloor heating    | EN 12667      |  | Suitable  |
| Residual indentation  | EN 433        |  | ≤ 0,35 mm                                       |
| Reaction to fire      | EN 13501 - 1  |  | B <sub>s</sub> 1                                |
| Slipresistance        | DIN 51130     |  | slip resistant<br><b>R 10</b><br>Classification |



06  
EN 14041:2004



Expanded (cushioned) polyvinyl chloride floorcoverings

**EN 653**

**POLYFLOR**<sup>TM</sup>  
COVERING THE WORLD

CALL 1800 777 425

POLYFLOR.COM.AU