



Espresso

«4m»



NATURAL LOOK

Technical innovation of printing and embossing techniques results in the natural look of a real wooden floor.



GREATER DURABILITY AND EASY CLEANING

The protective top coat prevents scuffing and staining, making your floor easy to clean.



BOUNCEBACKABILITY

The resilient foam backing ensures 'bouncebackability' and appearance retention.



UNIQUE POLYMER CORE

The unique polymer core providing increased strength for improved resistance ripping and tearing during installation and usage.



10 YEARS GUARANTEE

POLYFLORTM
COVERING THE WORLD

CALL 1800 777 425

POLYFLOR.COM.AU

CE

06

EN 14041:2004



Expanded (cushioned) polyvinyl chloride floorcoverings

EN 653

PRODUCT INFORMATION

	NORM	SYMBOL	ESPRESSO
Classification	EN 685		23 / 31
Total thickness	EN 428		2,25 mm
Wearlayer	EN 429		0,25 mm
Width	EN 426		4 m
Standard length	EN 426		25 m
Total roll weight	-		210 kg

TECHNICAL INFORMATION

	NORM	SYMBOL	ESPRESSO
Light stability	ISO 105-B02		≥ 6
Dimensional stability	EN 434		≤ 0,40 %
Impact sound	EN ISO 717/2		Δ Lw 14 dB
Underfloor heating	EN 12667		Suitable
Residual indentation	EN 433		≤ 0,35 mm
Reaction to fire	EN 13501-1		B _{fl} S1
Slipresistance	DIN 51130		^{slip resistant} R10 Classification
Castor -chair test	EN425		Suitable