

Technical Data Sheet



Okatmos® star 150

Pressure Sensitive/Releasable Adhesive

- solvent-free
- easy application
- especially for self-laying carpet and carpet tiles
- especially for VCT-flooring

PROPERTIES AND USAGE

Solvent-free releasable adhesive for installation of self-laying carpet and carpet tiles with fleece-, PVC- or textile-backing. Also suitable for releasable installation of vinyl composite tiles (VCT). **Okatmos star® 150** can be used on false floors, wood particle board and metal, over PVC-, CV- and linoleum-coverings and on ceramic tiles (must be well bonded, sound, smooth and free of all waxes, finishes, strippers and cleaners) and any other subfloor ready for installation.

Coverings installed with **Okatmos® star 150** can be removed and reinstalled

For advanced Indoor-Air-Quality. Prevents odours originating in microbial interactions between the floor covering and the application surface.

SUBSTRATE PREPARATION

The substrate must comply with relevant installation standards as well as with all technical requirements and must be ready for installation. The surface must be sound and clean. Remove dirt, paint, oil, grease wax and other contamination which might act as a bondbreaker.

Old floor coverings must be free of care products e.g. wax and promote good bond characteristics with the substrate. If necessary, clean with **Okamul GR**.

Prime absorbent subfloors with **Okamul HD 11** or **Okatmos® EG 20**.

PROCESSING

Stir **Okatmos® star 150** well.

Apply the adhesive onto the substrate using a nap roller or notched trowel. When installing on false floors be sure to avoid material penetrating into the tile joints and stick. Install covering after the adhesive is thoroughly dry and press tightly.

Please note:

The fixative may stain certain substrates which will remain after the covering has been removed.

SPECIFICATIONS

Color	white
Application	interior
Minimum substrate temperature	+17°C
Ventilating time*	approx. 30 – 60 minutes
Open times*	unlimited
Floor heating systems	suitable
Marked according to GefStoffV regulations	no entry
GISCODE	D 1 according TRGS 610
Shelf live	store in frost protected area for up to 12 months

* At +20°C und 65 % relative humidity
 Higher temperatures and lower humidity decreases, lower temperature and high humidity increases this value respectively.

TOOLS AND COVERAGE

	Covering type	Coverage
shorthaired lambs wool roller	self laying carpet and carpet tiles	approx. 80 – 100 g/m ²
trowel TKB A2 V1	VCT-covering	approx. 140 g/m ²

CLEANING

Clean tools with water immediately after usage.

PACKAGING

<u>Packaging</u>	<u>Product Code</u>
5 kg oval plastic bucket	49063
15 kg oval plastic bucket	49062

The information is based on our experience and is to be regarded as general instructions. We cannot guarantee successful results since we do not have any influence on the conditions at the construction site and the proper processing. In any case a sample application is recommended before the installation.
 This data sheet replaces any previously issued data sheet.

02.03.09 Wbg.