



# Northstate

Simply better carpet.

# TERRATEX PRODUCT BULLETIN

Series 18L - Nylon

ABN 14010558540

<b>Fibre System</b>	Nylon 30% pre-consumer recycled content in face fibre
<b>Coloration</b>	100% Solution Dyed
<b>Construction</b>	Multi-Level Loop Pile
<b>Pile Weight</b>	18 oz/sq yd                      610.32 g/sq m
<b>Backing System</b>	Dual Latex bonding
<b>Primary Backing</b>	Woven Synthetic
<b>Secondary Backing</b>	100% Synthetic
<b>Carpet Protection</b>	Scoured & Extracted™ to remove processing oils PermaSeal™ stainblocker and soil release treatment Anti-microbial present in backing laminate
<b>Fire Hazard Properties</b> (B.C.A. Spec.C1.10a)	<b>Direct-Stick</b> - Tested to AS/ISO 9239-1 Suitable for ALL building classifications. <b>Conventional &amp; Double-Bond with underlay</b> - Tested to AS/ISO 9239-1 Suitable for ALL building classifications, <u>except non-sprinklered</u> Class 9a (Patient Care) and Class 3 (Accommodation for the Aged). <b>Verify building classifications with your local building authority and/or council.</b> <i>Consult your Northstate representative for specific details.</i>
<b>Static Generation (AS2834)</b>	< 3.0kv
<b>Light Fastness</b>	L6
<b>Change on Wet Cleaning</b>	Gray Scale 5
<b>Approx pattern repeat</b>	Not Applicable
<b>Installation Method</b>	Suitable for direct-stick or cushion installations
<b>Chair Protectors</b>	Mandatory under chairs with castors to preserve appearance retention, and avoid premature wear.
<b>Rating</b> <b>7 Year Commercial Limited Warranties</b> <i>see full warranty text for details</i>	Commercial Heavy Duty (including stairs) Abrasive Wear StainResist Anti-Shock ColourFast



#### Rating

Commercial Heavy Duty (including stairs)  
**7 Year Commercial Limited Warranties**  
Abrasive Wear                      ColourFast  
StainResist                              Anti-Shock  
*see full warranty text for details*



#### Fire Hazard Properties (B.C.A. Spec C1.10a)

**Direct-Stick** - Tested to AS/ISO 9239-1  
Suitable for ALL building classifications.  
**Conventional & Double-Bond with u/lay** - Tested to AS/ISO 9239-1  
Suitable for ALL building classifications,  
except non-sprinklered Class 9a (Patient Care) and  
Class 3 (Accommodation for the Aged)  
**Verify building classifications with your local building  
authority and/or council.**  
*Consult your Northstate representative for specific details.*



#### Environmentally Friendly

Solution Dyeing is an environmentally friendly dyeing method that  
conserves energy and uses 90% less water than conventional  
dyeing processes. *Product contains 30% pre-consumer recycled  
content in face fibre.*



#### Carpet Protection

- ♦ Scoured & Extracted™ to remove processing oils,
- ♦ PermaSeal™ stainblocker and soil release treatment,
- ♦ Anti-microbial present in backing laminate.

This carpet will look and perform better for longer, minimising  
re-soiling, enabling ease of spot cleaning and vacuuming, and  
ensuring lasting hygienic freshness.



#### Anti-Shock, Computer Friendly

This carpet will not generate a static shock exceeding 3.0 kV at  
relative humidity of 20% or more and a room temperature of 20° C.

- Installation to be in accordance with **Northstate Carpet Mills Technical Bulletin - Installation Procedures and Requirements, and ASNZS 2455.1:2007**. In direct-stick installations, all seams and cross joins must be sealed with a seam sealing adhesive. In double-bond and carpet gripper installations, all edges to be seamed must be sealed first with an edge sealing adhesive and an appropriate hot-melt adhesive seaming tape must be applied to all seams and cross joins. All unprotected edges must be sealed with an edge sealing adhesive.
- Northstate Carpet Mills manufactures to a high degree of quality however there are certain visual aspects in making of carpet that must be regarded as within manufacturing limits and do not affect the performance of the carpet.
- Pattern carpet with directional designs may be subject to pattern distortion. Exact colour &/or texture pattern match cannot be guaranteed.
- Carpets with linear designs and in particular, carpets constructed with contrasting colours side by side to produce a sisal effect may be subject to random colour banding across the carpet.
- Due to dyelot variations, actual material may vary from sample.
- Full details and explanations can be found on our website [www.northstatecarpets.com.au](http://www.northstatecarpets.com.au)
- Supporting our *ECO-focused* initiative, Northstate Carpet Mills where ever possible, use recycled, recyclable and bio-degradeable materials.

NORTHSTATE CARPET MILLS PTY LTD reserves the right to modify this specification to improve the product without prior notice and without prejudice.

E & O E