

# Polyflor Mediterranean Collection

Domestic Cushion Vinyl

## *Range 1 Data Information*


**Width:** 2m & 3m

**Thickness:** 2.00mm


**Wear Layer:** 0.15mm

**Warranty:** 5 Years

**Slip Resistance:** R10



Boston Steel 911D



Metro Slate 909E



Metro Granite 900D



Coney Honey Oak  
266M



Coney Boardwalk Oak  
006M



# Polyflor Mediterranean Collection

Domestic Cushion Vinyl

## **Range 2 Data Information**

**Width:** 2m & 3m

**Thickness:** 2.40mm

**Wear Layer:** 0.20mm

**Warranty:** 5 Years

**Slip Resistance:** R10



Celina Tile 109M



Aveo 168M



Canyon 637M



Vero 796L



Aria 911L



Canyon 967D



Aged Oak 967M



Aria 979M



Aveo 090S



*Canyon 637M*

# Polyflor Mediterranean Collection

Domestic Cushion Vinyl

**Range 1 Data Information**



Guarantee

Garantie

Garantie

Garantie



	Product information Produkt informatie	Produkt Daten Information produit		
	Total thickness Totale dikte	Gesamtstärke Epaisseur totale	EN 428	2,00 mm
	Wearlayer Slijtlaag	Nutzschicht Couche d'usure	EN 429	0,15 mm
	Width Breedte	Breite Largeur	EN 426	2m 3m 4m
	Standard length Standard rollengte	Standard Rollenlänge Longueur standard	EN 426	32 m
	Total weight Totaal gewicht	Total gewicht Poids total		1200 g/m <sup>2</sup>
	Classification Classificatie	Klassifizierung Classification	EN 685	21 Domestic moderate

	Technical information Technische informatie	Technische Daten Information technique		
	Light stability Lichtechtheid	Lichtechtheit Résistance à la lumière	ISO 105-B02	≥ 6
	Dimensional stability Dimensionele stabiliteit	Dimensionsstabilität Stabilité dimensionnelle	EN 434	≤ 0,40%
	Underfloor heating Vloerverwarming	Fussbodenheizung Chauffage par le sol	EN 12667	Suitable Geschikt Geeignet Convenable
	Residual indentation Restindrukking	Eindruckverhalten Poinçonnement	EN 433	≤ 0,35 mm
	Reaction to fire Brandklasse	Brandverhalten Indice d'incendie	EN 13501-1	B <sub>f</sub> S1
	Slipresistance Slipweerstand	Rutschhemmung Glissance	DIN 51130	

# Polyflor Mediterranean Collection

Domestic Cushion Vinyl

*Range 2 Data Information*



## Product Information

Usage classification	EN ISO 10874 EN 685		22
Wear layer	EN ISO 24340 EN 429		0,20 mm
Total thickness	EN ISO 24346 EN 428		2,40 mm
Total weight	EN ISO 23997 EN 430		1350 g/m <sup>2</sup>
Standard widths	EN ISO 24341 EN 426		2 - 3 - 4 m
Standard length	EN ISO 24341 EN 426		30 m

## Technical Information

Light stability	EN ISO 105 B02		≥ 6
Dimensional Stability	EN ISO 23999 EN 434		≤ 0,40 %
Underfloor heating	EN 12667		Suitable
Residual Indentation	EN ISO 24343-2 EN 438		≤ 0,35 mm
Reaction to fire	EN 13501-1		Bfl/S1
Slip resistance	DIN 51130		R10
Impact sound	EN ISO 7172		Δ Lw 16 dB