

- Polyflor Expona PUR features a high quality, cross-linked polyurethane reinforcement, UV cured to provide superior cleaning benefits and life cycle maintenance savings.
- The following maintenance instructions are designed to minimise the cost factor, without compromising the long-term appearance of your floorcovering.



INITIAL CONSTRUCTION CLEAN

- Remove all loose debris.
- Ensure that all traces of adhesive are removed from the surface of the floorcovering.
- Mop sweep or vacuum to remove dust and grit.
- Damp mop with a neutral detergent.
- If required, dry buff with a 1000 rpm plus rotary machine fitted with a suitable clean pad.



ROUTINE MAINTENANCE

• The following recommendations are provided as a guideline, and the frequencies can be changed to optimise the appearance.

DAILY

- Mop sweep or vacuum to remove dust and loose dirt.
- If required, spot clean to remove stubborn marks with a neutral cleanser.
- If required, dry buff to restore finish.

WEEKLY/MONTHLY

- Assess the appearance of the floor.
- If required, scrub with a scrubber dryer fitted with suitable pads, and using neutral cleanser (pH 7 to 9).
- If required, dry buff to restore finish.



APPLICATION OF A FLOOR DRESSING

- Should you wish to apply a floor dressing to the floorcovering to provide extra protection in heavily trafficked areas, please follow details of the procedure below.
- Using an applicator and tray, or Kentucky mop with wringer and bucket, the first coat should be applied thinly and evenly across the floor, to within 200mm of the skirtings. It should then be left to dry.
 This normally takes approximately thirty minutes, depending on the ambient conditions and the thickness of the coating.
- When the first coat is dry, a second coat should be applied at right angles to the direction of the first. Subsequent coats should be applied at right angles, and the final coat should be applied right up to the skirting.
- Two to three thin coats are usually sufficient to provide excellent resistance to abrasion, scuffing and removal of black heel marking. However, be guided by your own periodic assessments for the particular location.
- In order to minimise costs, subsequent polish applications may be applied only to traffic paths.
- Periodically generally every six months assess the appearance of the floor. If there is an unacceptable build-up of polish, this should be stripped and reapplied, as per the instructions above.



 $\mbox{{\it NOTE:}}$ The maintenance regime requires the installation of an effective barrier matting system.

Cleaners and detergents should be diluted as per the manufacturers' instructions.

These maintenance instructions are intended for Polyflor Expona PUR, which incorporates a polyurethane reinforcement.

For other Polyflor products, reference should be made to their specific floorcare sheets.

 For further information and advice on specific applications, consult Polyflor Customer Technical Services on +44 (0)161767 1912, or email tech@polyflor.com.

Always follow the Health and Safety guidance provided.

• At the date of issue the data presented is correct.

However, Polyflor Ltd. reserve the right to make changes which do not adversely affect performance or quality.

REGULAR CLEANING IS MORE BENEFICIAL TO THE FLOORCOVERING AND MORE COST-EFFECTIVE THAN OCCASIONAL HEAVY CLEANING.





FLOORCARE FOR EXPONA COMMERCIAL AND EXPONA DESIGN







MAINTENANCE Products

APPROVED MAINTENANCE PRODUCTS

The companies listed have products that are approved for use with Polyflor products. For full instructions for use, and health and safety guidelines, please contact the manufacturer.

					1		
PRODUCT	DR. SCHUTZ Tel: 01296 437827 www.dr-schutz.com	BRITISH NOVA Tel: 01295 254030	PROCHEM Tel: 0208 974 1515 www.prochem.co.uk	EVANS VANODINE Tel: 01772 322200 www.evansvanodine.co.uk	ECOLAB LTD Tel: 01793 511221 www.ecolab.com	DIVERSEY UK LTD Tel: 01604 405311 www.diversey.com	SELDEN RESEARCH Tel: 01298 26226 www.selden.co.uk
NEUTRAL CLEANSER	Active Cleaner	Liquid 99	Prodet	High Class	Brial Action Plus	Taski Jontec 300 Carefree	Neutral Scrubber Drier Detergent
						Stride 1000	Sabre
ALKALINE CLEANSER	Clean and Strip	Novaways	Alkleen	E.M.C Plus	Gloss Express	Brillo Cleaner/ Degreaser	Multi-Purpose Cleaner
		Novaways Multi Purpose Sanitiser	Ultrapac Renovate	Versatile	Regain Regain Ultra	Carefree Stride 2000	Selclen S
		Jameser	Powerclean	Lift	Powerclean	Sprint Hard Surface Cleaner	Triple
				HSC	Imi Action Plus	Taski Jontec Forward	
GERMICIDAL CLEANSER		Novacross Non food areas	Protect	Final Touch		Lifeguard Cleaner/ /Disinfectant Conc.	Selgiene
		Novacross (unperfumed)		Safe Zone		Shield	Selgiene Ultra
		Food areas		Protect		Lifeguard cleaner DisinfectantTrigger	Selactive
MAINTAINER/ WASH & WAX	Floor Cleaner R1000	Novacare	Protreat	Clean & Shine	Indur XL Fresh	Carefree Maintainer	Selsheen
		Novacare Lime-lite			Indur Brillant Plus	Carefree Mop & Shine	Fast Lane
					Satine Brilliant Plus	Carefree Stride 3000	Low Foam Floor Maintainer
					Indur Restorer Spray	Taski Tensol	
DRY BRIGHT EMULSION	Floor Shine	Nova Long Life	Proshine	Sustain	Isi Star	Carefree Satin	Seldur
POLISH		Nova Long Life Satin Finish		Mexepol	Phazer Isi Star	Carefree Eturnum	Selexel
				Enhance	Gemstor Laser	Carefree Emulsion	Diamond Brite
					Satin Star		
					Tuklar Medical		
SEMI BUFFABLE EMULSION POLISH	Floor Mat	Nova Supercote				Carefree Buffable Floor Polish	Selglo
FULLY BUFFABLE EMULSION POLISH	Secura Hard Sealer	Nova Superphalte	Proshine		Tuklar Medical		
POLISH	Clean & Strip	Nova Starbrite	Prostrip	Easystrip	Bendurol Maxx	Carefree Stripper	Selstrip
STRIPPER					Bendurol Forte		Selspeed
		Nova 2001		Sure Strip	Bendurol Top Strip	Carefree Speed Stripper	Selate
POWER CLEANER (Spot Cleaner)	Turbo Strip	Cleanol Lift	Superclean	Lift		Sprint Spitfire	Maxima

The data presented is correct at the time of printing. However, Polyflor Ltd. reserves the right to update this information as and when necessary. For the latest information, please check our web site at www.polyflor.com

Polyflor Ltd, in providing this information, does not imply any equivalence between each of the different manufacturers' products, or that other products would prove unsatisfactory.

POLYFLOR LTD. PO BOX 3 RADCLIFFE NEW ROAD WHITEFIELD MANCHESTER M45 7NR UK UK SALES DIRECT: +44 (0)161 767 1122 UK SAMPLE REQUESTS: +44 (0)161 767 2551 EXPORT SALES DIRECT: +44 (0)161 767 1913 TECHNICAL SUPPORT: +44 (0)161 767 11912 RECEPTION: +44 (0)161 767 1110 UK FAX: +44 (0)161 767 1128 EXPORT FAX: +44 (0)161 767 1166 E-MAIL: INFO@POLYFLOR.COM

WEBSITE: WWW.POLYFLOR.COM

FLOORING



