

Launch Document

Domestic Cushion Vinyl

Secura
luxury vinyl sheet flooring

Combining influences from natural textures like wood and stone through to contemporary modern living materials, the Secura collection of 26 wood, stone and abstract designs has been developed to enhance domestic interiors using authentic and inspiring patterns, whilst offering the practicality and durability that comes from luxury vinyl sheet flooring.

The Secura collection has been designed to be used in every room in the home. Innovative maintenance and slip resistance technology, together with an eclectic array of traditional and contemporary designs provides a finish that can be enjoyed for years to come.

Secura can be installed over underfloor heating. Please note it is recommended that underfloor heating systems are commissioned prior to the flooring being installed to ensure the heating system is operating correctly.

- Available in 2m roll widths only
- Impact sound reduction of 19dB, exceeding current building regulations
- Featuring a polyurethane reinforcement (PUR) for improved cleaning and maintenance
- R10 slip resistance (for sustainable wet slip resistance refer to Polysafe ranges)
- 0.35mm wear layer, ideal for light commercial interiors
- BRE Global environmental A rating (Generic)*
- 100% recyclable
- 20 year warranty



26 Stocked Colours in 2m wide only




Yorkstone 2110



Limestone 2111



Peakmoor Sandstone 2112




African Mahogany 2134



Alabaster Elm 2123



Antique Herringbone 2129



Antique Oak 2131



Aspen 2124



Black Walnut 2133



Black Slate 2114



Blond Oak 2127



Country Oak 2130



Ebony 2135



Farmhouse Terracotta 2113




Golden Oak 2128




Grey Flagstone 2119



Linear Charcoal 2122



Linear Fawn 2121



Linear Ivory 2120



Natural Oak 2126



Norwegian Maple 2125



Polished Concrete 2118




Riviera Bluebell 2117



Riviera Sands 2115



Riviera Taupe 2116



Sweet Chestnut 2132

Technical Information

Specifications	Standards	Secura
Type of Floorcovering	EN 653 EN ISO 26986	Heterogeneous Heterogeneous
Product Enhancement		PUR
Gauge	EN 428 EN ISO 24346	3.0mm
Wear Layer	EN 429 EN ISO 24340	0.35mm
Performance Classification	EN 685 EN ISO 10874	23, 32, 41
Roll Size	EN 427 EN ISO 24341	2m x 25m = 50m ²
Total Weight	EN 430 EN ISO 23997	1,780g/m ²
Acoustic Impact Sound Reduction	EN ISO 10140-3 (EN ISO 140-8)	19dB
Residual Indentation	EN 433 EN ISO 24343-1	≤ 0.2mm
Abrasion Resistance	EN 649	Group T
Dimensional Stability	EN 434 EN ISO 23999	≤ 0.40%
Behaviour to Fire	EN 13501-1	Bfl
Slip Resistance	DIN 51130 EN 13893	R10* Class DS (Dry Condition)
Light Fastness	ISO 105-B02(Method 3)	≥ 6
Resistance to Chemicals	EN 423 (ASTM F 1303-99)	Excellent
Underfloor Heating Suitability	ISO 8302	Suitable (Max 27°C)
Castor Chair Suitability	ISO 4918	Pass
VOC Test	Indoor Air Comfort Gold AgBB	Approved Very low emissions
Electrical Behaviour (body voltage)	EN 1815	This product does not accumulate static charges above 2kV and is classified as 'antistatic'. For specialist applications where there is requirement to dissipate the electrostatic charge, see the Polyflor ESD product range.
Hygiene	This product has been independently tested and results demonstrate that it inhibits the growth of MRSA. An effective cleaning regime is however, the most important defence against infection.	
Environmentally Preferable Flooring	Polyflor Secura PUR achieves a BRE Global Environmental A Rating (Generic) in major use areas such as education and healthcare. Polyflor Secura PUR is 100% recyclable. EN 15804 Environmental Product Declaration is available upon request, and a full Environmental Report detailing Polyflor's achievements in areas such as recycling, energy reduction and waste avoidance can be found at www.polyflor.com/environment .	

*for commercial installations that require sustainable wet slip resistance, refer to the Polysafe ranges.

